

The DTU-1141 is Wacom's premium product that is specifically designed for viewing and signing electronic documents directly on screen.

The 10.6" LCD size is large enough to comfortably read text, yet has a small enough footprint to fit easily in any business environment. The generous screen size makes it ideal to show slide shows, videos, and other promotional material when not used for signing.

The ability to perform secure transactions is the strength of the DTU-1141. The DTU-1141 includes state-of-the-art encryption, and unique hardware ID (UID) to pinpoint the exact unit used for any digital signature.

The DTU-1141 can be easily integrated into existing installations and runs on Windows and Macintosh systems. The flat glass surface is comfortable for signing and writing, and allows the unit to be mounted into tables and desks. Standard VESA mounting holes are provided for use with 3rd party arms and stands. The cover glass has anti-glare properties with a superb paper-like feel, and is highly scratch-resistant. There is a Kensington Security Slot to prevent theft and the pen tether ensures the pen will not be lost.

Features and benefits:

- View and sign A4 and Letter-size documents with minimal scrolling and shrinking
- 10.6" IPS LCD boasts full colour, Full HD resolution (1920 x 1080) and wide viewing angle
- Supports multiple resolutions from 800 x 600 to 1920 x 1080 to match any application
- Large screen is ideal for showing promotional materials when not used for signing
- Just one USB cable for power to reduce clutter
- State-of-the-art encryption to ensure secure transactions
- Unique hardware ID (UID) to identify the exact unit used for any transaction
- Uses Wacom's patented cordless and battery-free pen with 1024 levels of pressure
- 4 capacitive-touch ExpressKeys for easy access to commonly used shortcuts
- Integrated stand allows the DTU-1141 to be used flat, or at a comfortable angle
- VESA mounting holes are included to attach to 3rd party arms and stands
- The cover glass contains anti-glare properties and has a natural, paper-like feel
- Kensington Security Slot prevents theft
- Beautiful industrial design adds elegance to any workspace
- Can be easily integrated into existing installations and is extremely durable



DTU-1141

General Specifications

| | |
|--|--|
| Dimensions (W x H x D, excluding stand) | 283 x 210 x 11 mm (excluding rubber stand foot) 283 x 210 x 16 mm (including rubber stand foot) |
| Weight (including stand) | 700 grams |
| Body color | Black |
| Stand inclination | 15° |
| Power supply | USB bus power, no AC power required |
| Power consumption | 5W maximum, 1W in sleep mode |
| Communication interface | USB 2.0 (high speed) |
| Supported operating systems | Windows XP / 7 / 8 / 8.1 Mac OS 10.7 and later |

LCD Screen

| | |
|------------------------|--|
| Screen size | 10.6" |
| Aspect ratio | 16:9 |
| Display type | IPS TFT display |
| Cover glass surface | Tempered anti-glare etched glass |
| Native resolution | 1920 x 1080 |
| Supported resolutions | 800 x 600, 1.024 x 600, 1.024 x 768, 1.280 x 800, 1.440 x 900, 1.920 x 1.080 |
| Viewing angles | 170° / 170° |
| Colours | 16.7M colors |
| Luminance (brightness) | 200 cd/m ² (typical) |
| Contrast ratio | 800:1 (typical), 600:1 (min) |
| Response time | 16 ms (typical) |
| Backlight lifetime | 20.000 hours |

Tablet and pen

| | |
|-----------------------|--|
| Technology | Electromagnetic Resonance (EMR) |
| Active area | 235 x 132 mm |
| Pressure levels | 1.024 |
| Coordinate resolution | 2540 lpi or 0.01 mm/pt |
| Coordinate accuracy | ±0.5 mm / ±0.02 inch (center) |
| Report rate | 200 points per sec. (non interpolated) |
| Reading height | 5 mm or more (center) |

Miscellaneous

| | |
|--|---|
| Pen storage | Integrated pen compartment, pen holder |
| Graphics card | Any graphics card |
| Wall mount | VESA 75 mm |
| Software | Compatible with E-signature software, Wacom's SDKs and Wacom's sign pro PDF |
| Drivers | Wacom driver and DisplayLink driver required |
| Package content | Interactive pen display with integrated stand, cordless and battery-free pen, USB Y-cable (3 m / 9.84 ft), installation CD (Wacom driver, DisplayLink driver, product information), quick start guide, pen tether, 5 extra pen nibs, nib removal tool, 4 VESA mounting screws, pen compartment cover, USB plug attachment |
| Operating temperature, relative humidity | +5° to +40° C / +41° to +104° F, 30% to 80% (non-condensing) |
| Storage temperature, relative humidity | 20° to +60° C / -4° to +140° F, 30% to 90% (non-condensing) |
| Warranty | May vary depending on country of purchase |

