





Wacom STU-530



Thin, robust and secure
The STU-530 brings colour to
counters and check-outs.

General	Spec	ificat	ions

Dimensions	161 x 174 x 11 mm
(W x H x D, excluding stand)	
Weight (including stand)	270 g
Power supply	via USB, no additional power adapter required
Power consumption	5W maximum
Communication interface	USB 2.0 (high speed)
Supported operating systems	Windows® Vista, 7, 8, 10

LCD Screen

Front cover	dark grey
Main body colour	black
Display type	Amorphous TFT LCD, colour, LED backlight
Cover plate surface	Tempered anti-glare etched glass with anti-reflective coating
Screen diagonal	5.0 inch
Resolution	WVGA, 800 x 480 pixels
Viewing angles (horizontal/vertical)	140° / 120°
Colours	True colour (16,7 million colours)
Luminance (brightness)	200 cd/m2 (typ)
Contrast ratio	600:1

Tablet and pen

rabiot and pon	
Technology	electromagnetic resonance (EMR)
Active area	108.0 x 64.8 mm
Resolution	2.540 lpi (non-interpolated)
Coordinate accuracy	±0.02 inch / 0.5 mm (center)
Report rate	200 points per sec. (non-interpolated), 800 4D coordinates
Pressure levels	1.024 (non-interpolated)
Reading height	0.2 inch / 5 mm (center)
Pen storage	Integrated pen compartment
Encryption	AES 256 bit encryption, RSA 2048 bit key exchange

Miscellaneous

Graphics card	Not needed
Software	Compatible with signature / E-signing software and Wacom's sign I pro PDF, C++,.Net and Java SDK/API available for developers
Package content	Signature pad, cordless and battery-free pen, USB cable, (9.84 ft / 3 m), quick start guide, pen tether (nylon fiber, 19.7 inch / 50 cm)
Operating temperature, relative humidity	5 to 40 degrees C, humidity: 30% to 80% RH (non-condensing)
Storage temperature, relative humidity	-20 to 60 degree C, Humidity: 30% to 90% RH (non-condensing)
Warranty	Depending on region and channel of purchase – please inquire for details